



RIKA Innovative Ofentechnik GmbH
AT-4563 Micheldorf, Müllerviertel GmbH
20
74-CPR-07.2013

EN14785:2006**Notified Body:** 1746**Intended use:** Space heating in residential buildings without possible supply of hot water**Name:** DOMO BACK / DOMO BACK MA**Description:** space heating appliances fired by wood pellets - system 3

Height		1370 mm
Width		772 mm
Depth		428 mm
Fire safety		pass
Safety distance to combustible material	rear	100 mm
	sides	100 mm
	top	500 mm
	front	800 mm
	floor	12 mm
Emission of combustion products		pass
CO-Emission at nominal heat output		< 0,02 %
CO-Emission at nominal heat output		< 0,25 g/Nm ³
Release of dangerous substances		NPD
Surface temperature		pass
Electrical safety		pass
Cleanability		pass
Durability		pass
Mechanical resistance (to carry chimney)		NPD
Maximum operating pressure		not applicable
Flue gas temperature at the measuring section at nominal heat output		178,1 °C
Flue gas temperature outlet at nominal heat output		213,7 °C
Thermal output		pass
Nominal- / part load heat output	10 kW	3 kW
Nominal- / part load space heat output	10 kW	3 kW
Nominal- / part load water heat get output folder path	not applicable	not applicable
Efficiency		pass
Nominal- / part load Efficiency	91%	91,9 %
recommended fuel type		wood pellets (ISO 17225-2)
Suitability for installation to a shared flue system		yes
Emission (addition)		
CO wood pellets PM wood pellets OGC wood pellets NO _x wood pellets	g/Nm ³	< 0,25
	g/Nm ³	< 0,02
	g/Nm ³	< 0,06
	g/Nm ³	< 0,20
Emission (requirements according AT 15A)		
CO wood pellets PM wood pellets OGC wood pellets NO _x wood pellets	mg/MJ	< 500
	mg/MJ	< 25
	mg/MJ	< 30
	mg/MJ	< 100
Pleas read manufacturer's operating instructions carefully before installing and using the appliance!		



Innovative Ofentechnik GmbH
A-4563 Micheldorf, Müllerviertel 20
Tel.: +43 (0)7582/686-14, Fax DW: -43
www.rika.at

Signed on behalf of the manufacturer

Andreas Bloderer / product manager

Name and function

Micheldorf, 14.12.2021

Place and date of issue