

MODEL				ASH-24BIS/W, ASH-24BIS/B			
FUNCTION				FUNCTION			
Cooling	Yes			Average season	Yes		
Heating	Yes			Warmer season	Yes		
				Colder season	Yes		
Design load				Seasonal efficiency			
Item	symbol	value	unit	Item	symbol	value	unit
Cooling	Pdesignc	7,00	kW	Cooling	SEER	7,00	--
Heating / Average	Pdesignh	6,40	kW	Heating / Average	SCOP/A	4,00	--
Heating / Warmer	Pdesignh	7,10	kW	Heating / Warmer	SCOP/W	5,20	--
Heating / Colder	Pdesignh	6,40	kW	Heating / Colder	SCOP/C	3,40	--
Declared capacity for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj				Declared energy efficiency ratio, at indoor temperature 27(19)°C and outdoor temperature Tj			
Item	symbol	value	unit	Item	symbol	value	unit
Tj = 35 °C	Pdc	7,09	kW	Tj = 35 °C	EERd	3,54	--
Tj = 30 °C	Pdc	5,03	kW	Tj = 30 °C	EERd	5,46	--
Tj = 25 °C	Pdc	3,29	kW	Tj = 25 °C	EERd	7,61	--
Tj = 20 °C	Pdc	2,86	kW	Tj = 20 °C	EERd	13,59	--
Declared capacity for heating/Average season, at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance / Average season, at indoor temperature 20 °C and outdoor temperature Tj			
Item	symbol	value	unit	Item	symbol	value	unit
Tj = - 7 °C	Pdh	5,68	kW	Tj = - 7 °C	COPd	2,67	--
Tj = 2 °C	Pdh	3,45	kW	Tj = 2 °C	COPd	4,06	--
Tj = 7 °C	Pdh	2,23	kW	Tj = 7 °C	COPd	4,91	--
Tj = 12 °C	Pdh	2,07	kW	Tj = 12 °C	COPd	6,05	--
Tj = operating limit	Pdh	5,58	kW	Tj = operating limit	COPd	2,53	--
Tj = bivalent temperature	Pdh	5,68	kW	Tj = bivalent temperature	COPd	2,67	--
Declared capacity for heating / Warmer season, at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance / Warmer season, at indoor temperature 20 °C and outdoor temperature Tj			
Item	symbol	value	unit	Item	symbol	value	unit
Tj = 2 °C	Pdh	7,12	kW	Tj = 2 °C	COPd		--
Tj = 7 °C	Pdh	4,57	kW	Tj = 7 °C	COPd		--
Tj = 12 °C	Pdh	2,06	kW	Tj = 12 °C	COPd		--
Tj = operating limit	Pdh	7,12	kW	Tj = operating limit	COPd		--
Tj = bivalent temperature	Pdh	7,12	kW	Tj = bivalent temperature	COPd		--
Declared capacity for heating / Colder season, at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance / Colder season, at indoor temperature 20 °C and outdoor temperature Tj			
Item	symbol	value	unit	Item	symbol	value	unit
Tj = - 7 °C	Pdh	3,91	kW	Tj = - 7 °C	COPd	2,91	--
Tj = 2 °C	Pdh	2,37	kW	Tj = 2 °C	COPd	4,16	--
Tj = 7 °C	Pdh	1,57	kW	Tj = 7 °C	COPd	4,98	--
Tj = 12 °C	Pdh	2,26	kW	Tj = 12 °C	COPd	6,24	--
Tj = operating limit	Pdh	5,06	kW	Tj = operating limit	COPd	1,95	--
Tj = bivalent temperature	Pdh	5,71	kW	Tj = bivalent temperature	COPd	2,13	--
Tj = - 15 °C	Pdh	–	kW	Tj = - 15 °C	COPd	–	--
Bivalent temperature				Operating limit temperature			
Item	symbol	value	unit	Item	symbol	value	unit
Heating / Average	Tbiv	-7	°C	Heating / Average	Tol	-10	°C
Heating / Warmer	Tbiv	2	°C	Heating / Warmer	Tol	2	°C
Heating / Colder	Tbiv	-15	°C	Heating / Colder	Tol	-20	°C
Cycling interval capacity				Cycling interval efficiency			
Item	symbol	value	unit	Item	symbol	value	unit
For cooling	Pcycc	x,x	kW	For cooling	EERcyc	x,x	--
For heating	Pcyh	x,x	kW	For heating	COPcyc	x,x	--
Degradation co-efficient cooling	Cdc	x,x	--	Degradation co-efficient heating	Cdh	x,x	--
Electric power input in power modes other than 'active mode'				Annual electricity consumption			
Off mode	P _{OFF}	0,000421	kW	Cooling	Q _{CE}	350	kWh/a
Standby mode	P _{SB}	0,000421	kW	Heating / Average	Q _{HE}	2240	kWh/a
Thermostat-off mode	P _{TO}	0,007579/0,011690	kW	Heating / Warmer	Q _{HE}	1912	kWh/a
Crankcase heater mode	P _{CK}	0	kW	Heating / Colder	Q _{HE}	3953	kWh/a
Capacity control				Other items			
Fixed	No			Sound power level (indoor/outdoor)	L _{WA}	65/70	dB(A)
Staged	No			Global warming potential	GWP	675	kgCO ₂ eq.
Variable	Yes			Rated air flow (indoor/outdoor)	--	900/3200	m ³ / h
Name and address of the manufacturer or of its authorised representative.				Manufacturer: SINCLAIR Corp. Ltd., 1-4 Argyll St., London, UK			
Contact details for obtaining more information				Representative: SINCLAIR EUROPE spol. s r.o., Purkynova 45, 612 00 Brno, CZ			
				info@sinclair-solutions.com / www.sinclair-solutions.com			

* R32 (100% HFC-32)

* Device contains fluorinated greenhouse gases covered by the Kyoto Protocol.