

					RXTM30RZV1 B	RXTM40RZV1 B
Sound pressure level	Heating		Nom.	dB(A)	49	49
	Cooling		Nom.	dB(A)	48	48
Standard Accessories	Installation manual				1	1
	Refrigerant charge label				1	1
	Multilingual fluorinated greenhouse gases labels				1	1
Refrigerant	Refrigerant=Charge=TCO2Eq			TCO2Eq	0.74	0.74
	GWP				675	675
	Charge			kg	1.1	1.1
	Type				R-32	R-32
Fan motor	Speed	Cooling	Super low	rpm	450	360
		Heating	Super low	rpm	360	360
Operation range	Cooling	Ambient	Max.	°CDB	46	46
			Min.	°CDB	-10	-10
	Heating	Ambient	Max.	°CWB	18	18
			Min.	°CWB	-25	-25
Piping connections	Level difference	IU - OU	Max.	m	15	15
	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 10m)	0.02 (for piping length exceeding 10m)
Dimensions	Unit		Width	mm	763	763
			Depth	mm	312	312
			Height	mm	551	551
Compressor	Type				Hermetically sealed swing compressor	Hermetically sealed swing compressor
Weight	Unit			kg	38	38
Power supply	Phase				1~	1~
	Frequency			Hz	50	50
	Voltage			V	220-240	220-240
Notes					(1) - Contains fluorinated greenhouse gases	(1) - Contains fluorinated greenhouse gases
					(2) - See separate drawing for operation range	(2) - See separate drawing for operation range
					(3) - See separate drawing for electrical data	(3) - See separate drawing for electrical data